

SINGAPORE STANDARD

SS 146 : Part 1 : 2008

IEC 60335-1 : 2006

(ICS 13.120; 97.030)

SPECIFICATION FOR

Household and similar electrical appliances – Safety

Part 1 : General requirements

Published by
SPRING Singapore
2 Bukit Merah Central
Singapore 159835
SPRING Singapore Website: www.spring.gov.sg
Standards Website: www.standards.org.sg

SINGAPORE STANDARD

SS 146 : Part 1 : 2008

IEC 60335-1 : 2006

(ICS 13.120; 97.030)

SPECIFICATION FOR

Household and similar electrical appliances – Safety

Part 1 : General requirements

All rights reserved. Unless otherwise specified, no part of this Singapore Standard may be reproduced or utilised in any form or by any means, electronic or mechanical, including photocopying and microfilming, without permission in writing from SPRING Singapore at the address below:

Head
Standardisation Department
SPRING Singapore
2 Bukit Merah Central
Singapore 159835
Telephone: 62786666 Telefax: 62786667
Email: stn@spring.gov.sg

ISBN 981-4154-62-8

CONTENTS

NATIONAL FOREWORD 8

FOREWORD 10

INTRODUCTION 14

1 Scope 15

2 Normative references 15

3 Definitions 19

4 General requirement 27

5 General conditions for the tests 27

6 Classification 30

7 Marking and instructions 31

8 Protection against access to live parts 37

9 Starting of motor-operated appliances 39

10 Power input and current 39

11 Heating 42

12 Void 46

13 Leakage current and electric strength at operating temperature 46

14 Transient overvoltages 49

15 Moisture resistance 50

16 Leakage current and electric strength 52

17 Overload protection of transformers and associated circuits 54

18 Endurance 54

19 Abnormal operation 55

20 Stability and mechanical hazards 64

21 Mechanical strength 65

22 Construction 66

23 Internal wiring 77

24 Components 79

25 Supply connection and external flexible cords 83

26 Terminals for external conductors 91

27 Provision for earthing 93

28 Screws and connections 95

29 Clearances, creepage distances and solid insulation 98

30 Resistance to heat and fire 105

31 Resistance to rusting 110

32 Radiation, toxicity and similar hazards 110

Annex A (informative) Routine tests	121
Annex B (normative) Appliances powered by rechargeable batteries	123
Annex C (normative) Ageing test on motors	126
Annex D (normative) Thermal motor protectors	128
Annex E (normative) Needle flame test	129
Annex F (normative) Capacitors.....	130
Annex G (normative) Safety isolating transformers.....	132
Annex H (normative) Switches	133
Annex I (normative) Motors having basic insulation that is inadequate for the rated voltage of the appliance	135
Annex J (normative) Coated printed circuit boards	137
Annex K (normative) Overvoltage categories.....	138
Annex L (informative) Guidance for the measurement of clearances and creepage distances.....	139
Annex M (normative) Pollution degree	141
Annex N (normative) Proof tracking test.....	142
Annex O (informative) Selection and sequence of the tests of clause 30.....	143
Annex P (informative) Guidance for the application of this standard to appliances used in warm damp equable climates.....	145
Annex Q (informative) Sequence of tests for the evaluation of electronic circuits	147
Annex R (normative) Software evaluation	149
Bibliography	150
Index of defined words	152
Figure 1 – Circuit diagram for leakage current measurement at operating temperature for single-phase connection of class II appliances	111
Figure 2 – Circuit diagram for leakage current measurement at operating temperature for single-phase connection of appliances, other than those of class II	112
Figure 3 – Circuit diagram for leakage current measurement at operating temperature for three-phase connection of class II appliances	113
Figure 4 – Circuit diagram for leakage current measurement at operating temperature for three-phase connection of appliances other than those of class II.....	114
Figure 5 – Void.....	114
Figure 6 – Example of an electronic circuit with low-power points	115
Figure 7 – Test finger nail.....	116
Figure 8 – Flexing test apparatus.....	117
Figure 9 – Constructions of cord anchorages	118
Figure 10 – An example of parts of an earthing terminal	119
Figure 11 – Examples of clearances	120
Figure I.1 – Simulation of faults	136
Figure L.1 – Sequence for the determination of clearances.....	139
Figure L.2 – Sequence for the determination of creepage distances.....	140
Figure O.1 – Tests for resistance to heat	143
Figure O.2 – Tests for resistance to fire	144

Table 1 – Power input deviation	40
Table 2 – Current deviation.....	41
Table 3 – Maximum normal temperature rises	44
Table 4 – Voltage for electric strength test	48
Table 5 – Characteristics of high-voltage sources.....	49
Table 6 – Impulse test voltage	49
Table 7 – Test voltages	53
Table 8 – Maximum winding temperature	57
Table 9 – Maximum abnormal temperature rise	63
Table 10 – Dimensions of cables and conduits	84
Table 11 – Minimum cross-sectional area of conductors	85
Table 12 – Pull force and torque	88
Table 13 – Nominal cross-sectional area of conductors	92
Table 14 – Torque for testing screws and nuts	97
Table 15 – Rated impulse voltage	99
Table 16 – Minimum clearances.....	99
Table 17 – Minimum creepage distances for basic insulation	103
Table 18 – Minimum creepage distances for functional insulation	104
Table A.1 – Test voltages	122
Table C.1 – Test conditions	126

National Foreword

This Singapore Standard was prepared by the Technical Committee on Safety of Household and Similar Electrical Appliances and Electronic Equipment under the purview of the Electrical and Electronic Standards Committee. It is a revision of SS 146 : Part 1 : 2004.

This standard is a identical adoption of the consolidated Edition 4.2 of International Standards IEC 60335-1 : 2001-05 (Edition 4.0) base publication, its two Amendments: IEC 60335-1 : 2004-03 Amendment 1 and IEC 60335-1 : 2006-05 Amendment 2 and its corrigenda of January 2002 and of December 2005.

A vertical line in the margin shows where the base publication has been modified by IEC amendments 1 and 2.

In this standard, the following print types are used:

- requirements : in roman type;
- test specifications : in italic type;
- notes : in small roman type;

Attention is drawn to the following:

1. Where the words 'International Standard' appear, they should be interpreted as 'Singapore Standard'.
2. The comma has been used throughout as a decimal marker in IEC 60335-1, whereas in Singapore Standards it is a practice to use a full-point on the baseline as the decimal marker.
3. Where the reference 'IEC 60335-1' or '60335-1 IEC' appears, it should be interpreted as 'SS 146 : Part 1'.
4. Where 'TC 61' appears, it should be interpreted as 'the national Technical Committee on Safety of Household and Similar Electrical Appliances and Electronic Equipment'.
5. The reference to IEC standards shall be replaced by the following Singapore Standards:

International Standard	Corresponding Singapore Standard
IEC 60227 (Parts 1, 2, 3 & 5)	SS 358 (Parts 1, 2, 3 & 5) Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V
IEC 60529	SS IEC 529 : 1989 Degrees of protection provided by enclosures (IP Code)
IEC 60598-1 : 2003	SS 263 : Part 1 : 2005 Luminaires - Part 1 : General requirements and tests
IEC 61032: 1997	SS 101 : 1999 Protection of persons and equipment by enclosures – Probes for verification

This Part 1 is to be used in conjunction with the appropriate part 2 of SS 146. The part 2 contains clauses to supplement or modify the corresponding clauses in Part 1, to provide the relevant requirements for each type of appliance.

Attention is drawn to the possibility that some of the elements of this Singapore Standard may be the subject of patent rights. SPRING Singapore shall not be held responsible for identifying any or all of such patent rights.

NOTE

1. *Singapore Standards are subject to periodic review to keep abreast of technological changes and new technical developments. The changes in Singapore Standards are documented through the issue of either amendments or revisions.*
2. *Compliance with a Singapore Standard does not exempt users from legal obligations.*

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES –
SAFETY –**

Part 1: General requirements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This part of international standard IEC 60335 has been prepared by IEC technical committee 61: Safety of household and similar electrical appliances.

This consolidated version of IEC 60335-1 is based on the fourth edition (2001) [documents 61/1965/FDIS and 61/1998/RVD], its amendment 1 (2004) [documents 61/2569/FDIS and 61/2639/RVD], its amendment 2 (2006) [documents 61/2996/FDIS and 61/3053/RVD] and its corrigenda of January 2002 and of December 2005.

It bears the edition number 4.2.

A vertical line in the margin shows where the base publication has been modified by amendments 1 and 2.

This part is to be used in conjunction with the appropriate part 2 of IEC 60335. The parts 2 contain clauses to supplement or modify the corresponding clauses in this part to provide the relevant requirements for each type of appliance.

Annexes B, C, D, E, F, G, H, I, J, K, M, N and R form an integral part of this standard.

Annexes A, L, O, P and Q are for information only.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

NOTE 1 The following annexes contain provisions suitably modified from other IEC standards:

– Annex E	Needle flame test	IEC 60695-11-5
– Annex F	Capacitors	IEC 60384-14
– Annex G	Safety isolating transformers	IEC 61558-1 and IEC 61558-2-6
– Annex H	Switches	IEC 61058-1
– Annex J	Coated printed circuit boards	IEC 60664-3
– Annex N	Proof tracking test	IEC 60112
– Annex R	Software evaluation	IEC 60730-1

NOTE 2 The following print types are used:

- requirements: in roman type;
- *test specifications: in italic type;*
- notes: in small roman type.

Words in **bold** in the text are defined in clause 3. When a definition concerns an adjective, the adjective and associated noun are also in bold.

The following differences exist in the countries indicated below.

- Clause 3: Steady conditions are defined (Poland).
- 3.4.2: Safety extra-low voltage shall not exceed 30 V (42,4 V peak) (USA).
- 5.7: The ambient temperature is 25 °C ± 10 °C (China, Japan and USA).
- 5.14: Accessible metal parts that are not liable to become energized (such as metal nameplates or decorative parts on a plastic enclosure) do not need to be earthed. Accessible non-metallic parts need only provide basic insulation (USA).
- 6.1: Class 0 appliances and class 0I appliances are not allowed (Australia, Austria, Belgium, Czech Republic, Finland, France, Germany, Greece, Hungary, India, Israel, Ireland, Italy, Netherlands, New Zealand, Norway, Poland, Singapore, Slovakia, Sweden, Switzerland, United Kingdom, Yugoslavia).
- 6.2: Protection against harmful ingress of water is determined by methods other than those given in IEC 60529 (USA).
- 7.1: The IP number is not required to be marked (USA).
- 7.6: Some of these symbols are not used (USA).
- 7.8: Additional methods are permitted for identifying earthing terminals and terminals for neutral conductors (USA).
- 7.12.2: The requirements for full disconnection do not apply (Japan, USA).
- 7.14: Different tests are used (USA).
- 8.1.1: The test is not necessarily repeated with the 20 N force (USA).
- 8.1.1: Protection against contact with live parts of the lamp cap is not required (USA).
- 8.1.2 and 8.1.3: The test probe 13 and test probe 41 are not used (USA).
- 8.1.5: Built-in appliances, fixed appliances and appliances delivered in separate units are not required to be protected by at least basic insulation before installation (USA).

- Clause 9: The ability of a motor to start without blowing a quick-acting fuse is required (USA).
- 10.1 and 10.2: Positive limits of 5 % for heating appliances and 10 % for motor-operated appliances are required and in general there are no negative deviations (USA).
- 11.4, 11.5 and 11.6: Heating appliances and heater circuits of combined appliances are operated at rated power input or rated voltage, whichever is the more severe; all other appliances and circuits are operated at rated voltage (USA).
- 11.8, table 3: Temperature rise limits for certain materials are different (USA).
- 13.2: The test circuit and some leakage current limits are different (India, USA).
- 13.3: The values of certain test voltages are different depending on the rated voltage (USA).
- 13.3: A 500 VA test transformer is used (USA).
- 15.1.1 and 15.1.2: The IP system is not used and the tests are different (USA).
- 15.3: The test is conducted with a relative humidity of $(88 \pm 2) \%$ at a temperature of $32 \text{ }^\circ\text{C} \pm 2 \text{ }^\circ\text{C}$ (USA).
- 16.2: The test is conducted at nominal supply voltage, and some of the leakage current values are different (USA).
- 16.3: Some test voltages and methods are different (USA).
- 19.1: The circuit protection device is permitted to provide necessary protection (USA).
- 19.2 to 19.4: Generally the tests are conducted at nominal supply voltage or rated power input (USA).
- 19.11: Different tests are carried out to evaluate solid state devices used in protective electronic circuits (USA).
- 19.13: The temperature rise limits of table 9 are not applicable (USA).
- 20.1: A stability test at 15° is not conducted, and an appliance tested in an overturned position is judged under abnormal test criteria (USA).
- 21.1: The impact force is applied by a falling steel ball instead of the spring hammer (USA).
- Clause 22: The d.c. component in the appliance neutral is limited (Australia).
- 22.1: The IP system is not used and the tests are different (USA).
- 22.2: The second paragraph of this subclause dealing with single-phase class I appliances with heating elements cannot be complied with because of the supply system (France and Norway).
- 22.2: Double-pole switches or protective devices are required (Norway).
- 22.2: Disconnection of the neutral is not necessary for all stationary appliances (USA).
- 22.2: The supply cord is not required to be fitted with a plug (Ireland).
- 22.3: The test is different (USA).
- 22.6: This test is not conducted (USA).
- 22.11: Different criteria for snap-on constructions are required (USA).
- 22.12: Positive forms of securement are required (USA).
- 22.14: Sharp edges are evaluated by means of a sharp edge testing device (USA).
- 22.35 and 22.36: Metal parts are generally not required to be separated by double or reinforced insulation (USA).
- 22.44: Appliances may be acceptable based on additional evaluation (USA).
- 22.46: The evaluation of software is different (USA).
- 23.5: Requirements for insulated internal wiring are different (USA).
- 23.7: The requirement only applies to wiring that is accessible when making supply connections (USA).
- 24.1.3: The number of cycles is different and the note does not apply (USA).
- 24.1.4: The number of cycles is different and note 1 does not apply (USA).
- 24.3: The requirement for full disconnection does not apply (USA).
- 25.1: The supply cord is not required to be fitted with a plug (Ireland).
- 25.3: A set of supply leads is not permitted (Norway, Sweden, Denmark, Finland, Netherlands).
- 25.3: The use of a set of terminals for connection of a flexible cord is not generally permitted (USA).
- 25.8: Conductor cross-sectional areas are different (Australia, New Zealand and USA).

- 25.8: 0,5 mm² supply cords are not allowed for class I appliances (Australia and New Zealand).
- 25.10: Green insulation is also permitted (USA).
- 25.13: Only one separate insulation is required (USA).
- 25.16: A pull of 35 lbs is applied except for small appliances. Generally the torque test is not applied (USA).
- 26.3: The tests only apply to terminals for connection to fixed wiring (USA).
- 26.6: Cross-sectional areas are specified according to American Wire Gauge (AWG) (USA).
- 27.6: The requirement does not apply (USA).
- 28.1: Generally, tests of this type are not required (USA).
- Clause 29: The requirements for clearances and creepage distances are different (USA).
- 29.1 Different rated impulse voltages are used between 50 V and 150 V (Japan).
- 29.3 The third dashed item of the test specification does not apply (Germany).
- 30.1: The minimum value for the ball-pressure test for parts retaining live parts is 95 °C or 40 K higher than the clause 11 temperature rise. For enclosures, the minimum value is 75 °C or a mould-stress test is conducted at 10 K above the clause 11 temperature (USA).
- 30.2.1: An ignition test cannot be used to assure a slow burning rate (USA).
- Annex B, 7.12: Appliances having non-replaceable batteries shall be marked with an appropriate symbol when the batteries have a content of mercury or cadmium exceeding 0,025 % by weight (Sweden and Switzerland).
- Annex B, 21.101: The requirement is different (USA).
- Annex I: The annex applies to motors having a working voltage not exceeding 30 V (USA).

INTRODUCTION

It has been assumed in the drafting of this international standard that the execution of its provisions is entrusted to appropriately qualified and experienced persons.

This standard recognizes the internationally accepted level of protection against hazards such as electrical, mechanical, thermal, fire and radiation of appliances when operated as in normal use taking into account the manufacturer's instructions. It also covers abnormal situations that can be expected in practice and takes into account the way in which electromagnetic phenomena can affect the safe operation of appliances.

This standard takes into account the requirements of IEC 60364 as far as possible so that there is compatibility with the wiring rules when the appliance is connected to the supply mains. However, national wiring rules may differ.

If the functions of an appliance are covered by different parts 2 of IEC 60335, the relevant part 2 is applied to each function separately, as far as is reasonable. If applicable, the influence of one function on the other is taken into account.

NOTE 1 Throughout this publication, when "Part 2" is mentioned, it refers to the relevant part of IEC 60335.

This standard is a product family standard dealing with the safety of appliances and takes precedence over horizontal and generic standards covering the same subject.

Individual countries may wish to consider the application of the standard, as far as is reasonable, to appliances not mentioned in a part 2, and to appliances designed on new principles.

An appliance that complies with the text of this standard will not necessarily be considered to comply with the safety principles of the standard if, when examined and tested, it is found to have other features which impair the level of safety covered by these requirements.

An appliance employing materials or having forms of construction differing from those detailed in the requirements of this standard may be examined and tested according to the intent of the requirements and, if found to be substantially equivalent, may be considered to comply with the standard.

NOTE 2 Standards dealing with non-safety aspects of household appliances are

- IEC standards published by TC 59 concerning methods of measuring performance;
- CISPR 11, CISPR 14-1, IEC 61000-3-2 and IEC 61000-3-3 concerning electromagnetic emissions;
- CISPR 14-2 concerning electromagnetic immunity.

HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES – SAFETY –

Part 1: General requirements

1 Scope

This International Standard deals with the safety of electrical appliances for household and similar purposes, their **rated voltage** being not more than 250 V for single-phase appliances and 480 V for other appliances.

Appliances not intended for normal household use but which nevertheless may be a source of danger to the public, such as appliances intended to be used by laymen in shops, in light industry and on farms, are within the scope of this standard.

NOTE 1 Examples of such appliances are catering equipment, cleaning appliances for industrial and commercial use, and appliances for hairdressers.

As far as is practicable, this standard deals with the common hazards presented by appliances that are encountered by all persons in and around the home. However, in general, it does not take into account

- persons (including children) whose
 - physical, sensory or mental capabilities; or
 - lack of experience and knowledgeprevents them from using the appliance safely without supervision or instruction;
- children playing with the appliance.

NOTE 2 Attention is drawn to the fact that

- for appliances intended to be used in vehicles or on board ships or aircraft, additional requirements may be necessary;
- in many countries additional requirements are specified by the national health authorities, the national authorities responsible for the protection of labour, the national water supply authorities and similar authorities.

NOTE 3 This standard does not apply to

- appliances intended exclusively for industrial purposes;
- appliances intended to be used in locations where special conditions prevail, such as the presence of a corrosive or explosive atmosphere (dust, vapour or gas);
- audio, video and similar electronic apparatus (IEC 60065);
- appliances for medical purposes (IEC 60601);
- hand-held motor-operated electric tools (IEC 60745);
- personal computers and similar equipment (IEC 60950);
- transportable motor-operated electric tools (IEC 61029).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.