

Specification for aluminium wood primer

AMENDMENT NO. 1

September 2014

1. Page 5, 5.2.1 Pigment

Replace “BS 1795” with “BS 1795 (partially replaced by ISO 3262)”.

2. Page 6, Table 2

Replace “Density” with “Density at 25 °C”.

3. Page 7, 5.4.5 Storage stability

Replace “specied” with “specified”.

4. Page 10, Standards referred to:

Replace with the following:

Standards referred to:

For undated references, the latest edition of the referenced document (including any amendments) applies.

BS 388	Specification for aluminium pigments
BS 1795	Specification for extenders for paints (partially replaced by ISO 3262)
*SS 5	Methods of test for paints, varnishes and related materials
Part A1	Sampling
Part A2	Examination and preparation of samples for testing
Part B2	Determination of non-volatile matter content
Part B3	Determination of water by the Dean and Stark method
Part B4	Condition in container
Part B5	Skinning (partially filled container)
Part B6	Storage stability (filled container)
Part B7	Density
Part B9	Brushing properties
Part B11	Determination of viscosity by Ford viscosity cup

Singapore Standard SS 38 : 1998
Amendment No. 1

Part B15	Determination of flash point – Closed cup equilibrium method
Part C2	Determination of aluminium metal content
Part C6	Determination of low concentrations of lead, cadmium and cobalt in paint by atomic absorption spectroscopy
Part D3	Hard-drying time
Part F1	Bend test (Cylindrical mandrel)

*NOTE – The review of the SS 5 series was completed in 2013.