



SINGAPORE STANDARD

Specification for aluminium alloy windows



Published by



SS 212 : 2007 (ICS 91.060.50)

SINGAPORE STANDARD Specification for aluminium alloy windows

All rights reserved. Unless otherwise specified, no part of this Singapore Standard may be reproduced or utilised in any form or by any means, electronic or mechanical, including photocopying and microfilming, without permission in writing from Enterprise Singapore. Request for permission can be sent to: standards@enterprisesg.gov.sg.

ISBN 981-4154-57-1

This Singapore Standard was approved by the Building and Construction Standards Committee on behalf of the Standards Council of Singapore on 12 September 2007.

First published, 1979 First revision, 1988 Second revision, 1998 Third revision, 2000 Fourth revision, 2007.

The Building and Construction Standards Committee appointed by the Standards Council consists of the following members:

		Name	Capacity
Chairman	:	Mr Goh Peng Thong	Standards Council
1 st Deputy Chairman	:	Er. Lee Chuan Seng	Standards Council
2 nd Deputy Chairman	:	Mr Tan Tian Chong	Standards Council
Secretary	:	Mr Kenneth Lim See Khoon	SPRING Singapore
Members	:	Mr Boo Geok Kwang	Singapore Civil Defence Force / Fire Safety and Shelter Department
		Er. Chan Ewe Jin	Institution of Engineers, Singapore
		Mr Chan Yew Kwong	Ministry of Manpower
		Mr Paul Fok	Land Transport Authority
		Mr Goh Ngan Hong	Singapore Institute of Surveyors and Valuers
		Mr Anselm Gonsalves	National Environment Agency
		Mr Desmond Hill	Singapore Contractors Association Limited
		Mr Joseph Lai Kuong Kiu	JTC Corporation
		Mr Benedict Lee Khee Chong	Singapore Institute of Architects
		Assoc Prof Leong Eng Choon	Nanyang Technological University
		Ms Andris Leong Sou Kwan	Building and Construction Authority
		Dr Lim Lan-Yuan	Association of Property and Facility Managers
		Mr McDonald Low	Real Estate Developers' Association of Singapore
		Mr Larry Ng Lye Hock	Urban Redevelopment Authority
		Assoc Prof Gary Ong Khim Chye	National University of Singapore
		Mr Davis Ong Wee Choon	Singapore Manufacturers' Federation
		Er. Shum Chee Hoong	Housing & Development Board
		Dr Tam Chat Tim	Individual Capacity
		Dr Tan Guan	Association of Consulting Engineers, Singapore

The Technical Committee on Architectural Works appointed by the Building and Construction Standards Committee and responsible for the preparation of this standard consists of representatives from the following organisations:

		Name	Capacity
Chairman	:	Mr Larry Ng Lye Hock	Member, B Committ

Member, Building and Construction Standards Committee

Deputy Chairman	:	Mr Benedict Lee Khee Chong	Member, Building and Construction Standards
			Committee
Secretary	:	Mr Han Kin Sew	SPRING Singapore
Members	:	Mr Choy Kin Man	TUV SUD PSB Pte Ltd
		Mr Gan Geok Chua	Singapore Glass Association
		Mr Koh Boon Pock	Singapore Timber Association
		Mr Lau Kwong Chung	Singapore Institute of Architects
		Major Lim Lam Kwang	Singapore Civil Defence Force
		Mr Low Leong Leong	Singapore Contractors Association Limited
		Mr Mok Kwong Wah	CPG Corporation Pte Ltd
		Mr Jeffery Neng Kwei Sung	Building and Construction Authority
		Mr Felix Quek Kwang Yong	Tile Association
		Er. See Sing Kok	Institution of Engineers Singapore
		Mr See Sing Mun	Singapore Manufacturers' Federation
		Mr Tang Chee Seng	Housing & Development Board
		Assoc Prof Tse Swee Ling	National University of Singapore
		Mr Wong Chung Wan	Setsco Services Pte Ltd
Co-opted Member	:	Mr Goh Chun Hee	Individual Capacity

The Working Group appointed by the Technical Committee to assist in the preparation of this standard comprises the following experts who contribute in their *individual capacity*:

		Name
Convenor	:	Mr Chew Kum Chong (till Jun 2006)
		Mr Tang Chee Seng
Members	:	Mr Chua Hock Kwan
		Mr Ho Kit Wing (till Oct 2006)
		Major Lim Lam Kwang
		Mr Raymond Tan
		Mr Tang Kum Luen
		Mr Wong Chee Hong

The organisations in which the experts of the Working Group are involved are:

Building and Construction Authority Compact Metal Industries Ltd Fire Safety & Shelter Department Housing & Development Board Kumpulan Akitek Lam Hong Leong Aluminium Pte Ltd Singapore Civil Defence Force TUV SUD PSB Pte Ltd YKK AP Singapore Pte Ltd

blank page

Contents

	Page
Foreword	 7

CLAUSES

1	General	
2	Definitions	
3	Window types and handing	
4	Materials	
5	Construction	
6	Work sizes and manufacturing tolerances	
7	Glazing	
8	Security	
9	Safety	
10	Performance	
11	Re-testing	
12	Report	
13	Modularly co-ordinated sizes	
14	Marking	

ANNEXES

А	Air leakage test	28
В	Watertightness test	34
С	Structural performance test	36
D	Proof load test	39
Е	Operation and strength tests	41
F	Recommended periods for calibration	51
G	Normative references	52

TABLES

1	Schedule of test requirements for operation test of windows	22
2	Operation of fasteners	23
3	Operation of sash	23
4	Preferred sizes for windows	27

SS 212 : 2007

Page

FIGURES

1	Window types (Elevations viewed from outside)
2a	Air leakage limits for opening lights of windows of air-conditioned buildings
2b	Air leakage limits for fixed lights of windows of air-conditioned buildings
3a	General arrangement of a typical test chamber (Exterior of test specimen facing inward of chamber)
3b	General arrangement of a typical test chamber (Exterior of test specimen facing outward of chamber)
4	Pressure sequence for air leakage test
5	Pressure sequence for watertightness test
6	Pressure sequence for structural performance and proof load test
7	Arrangement for resistance to excessive operating force (Test 3)
8	Arrangement for release of jammed sash (Test 4)
9	Arrangement for release of jammed hinge (Test 5)
10	Arrangement for strength of restricted opening and location system (Test 6)
11	Arrangement for resistance to accidental loading (Test 7)
12	Section showing dimensions "a" and "b"

Foreword

This Singapore Standard was prepared by the Technical Committee on Architectural Works under the purview of the Building and Construction Standards Committee.

It is a revision of SS 212 : 2000. The main changes in this revision are as follows:

- 1. Materials of fastenings and fixings shall be of stainless steel Type 304 (minimum). A new clause on the material and rigidity of stainless steel friction hinges is included. The clause specifies that the hinge shall be securely held by sufficient number of fastener in accordance with manufacturers' specifications.
- 2. Thickness of aluminium profile that receives the fixing of friction hinge shall be not less than 2.75 mm thick is recommended.
- 3. Definition and figure of full height windows are included. Windows or fixed glass panels below the height of barrier shall comply with Building Control Regulations. The use of laminated glass is recommended for the fixed glass panel below the height of barrier.
- 4. References to BS have been updated to BS EN wherever applicable.
- 5. Jumping track test requirement is introduced for sliding windows.

In preparing this specification, reference is made to the following publications:

1.	ASTM E 283 : 04	Standard test method for determining the rate of air leakage through exterior windows, curtain walls, and doors under specified pressures differences across the specimen
2.	ASTM E 330 : 02	Standard test method for structural performance of exterior windows, curtain walls, and doors by uniform static air pressure difference
3.	ASTM E 331 : 00	Standard test method for water penetration of exterior windows, curtain walls, and doors by uniform static air pressure difference
4.	BS 4873 : 2004	Specification for aluminium alloy windows
5.	BS 6375 : 1999	Performance for windows
		Part 1 – Classification for weathertightness (including guideline on selection and specification)
		Part 2 – Specification for operation and strength characteristics
6.	SS 381 : 1996	Materials and performance tests for aluminium curtain walls
7.	AAMA : 501	Methods of test for exterior walls

Acknowledgement is made for the use of information from the above publications.

Attention is drawn to the possibility that some of the elements of this Singapore Standard may be the subject of patent rights. Enterprise Singapore shall not be held responsible for identifying any or all of such patent rights.

NOTE

- 1. Singapore Standards (SSs) and Technical References (TRs) are reviewed periodically to keep abreast of technical changes, technological developments and industry practices. The changes are documented through the issue of either amendments or revisions.
- 2. An SS or TR is voluntary in nature except when it is made mandatory by a regulatory authority. It can also be cited in contracts making its application a business necessity. Users are advised to assess and determine whether the SS or TR is suitable for their intended use or purpose. If required, they should refer to the relevant professionals or experts for advice on the use of the document. Enterprise Singapore shall not be liable for any damages whether directly or indirectly suffered by anyone or any organisation as a result of the use of any SS or TR.
- 3. Compliance with a SS or TR does not exempt users from any legal obligations.

Specification for aluminium alloy windows

1 General

1.1 Scope

This Singapore Standard specifies materials, construction, finishes, hardware and performance standards for aluminium alloy windows. It also provides recommended co-ordinating sizes. This standard does not relate to secondary inner windows and louvre windows. For windows along open corridors, they do not have to be tested for watertightness. Any windows or fixed glass panels below the height of barrier shall comply with the Building Control Regulations.

1.2 Normative references

The reference documents in Annex G are indispensable for the application of this Singapore Standard. For dated references, only the edition cited applies. For undated references, the latest edition of the references document (including any amendments) applies.