

SINGAPORE STANDARD

**Methods of test for paints, varnishes and
related materials**

– Part G10 : Corrosion tests in artificial atmospheres – Salt
spray tests

SS 5 : Part G10 : 2020

ISO 9227:2017, MOD
(ICS 87.040; 77.060)

SINGAPORE STANDARD

Methods of test for paints, varnishes and related materials

– Part G10 : Corrosion tests in artificial atmospheres – Salt spray tests

Published by Enterprise Singapore

All rights reserved. Unless otherwise specified, no part of this Singapore Standard may be reproduced or utilised in any form or by any means, electronic or mechanical, including photocopying and microfilming, without permission in writing from Enterprise Singapore. Request for permission can be sent to: standards@enterprisesg.gov.sg.

© ISO 2017 – All rights reserved
© Enterprise Singapore 2020

ISBN 978-981-48-9480-7

The content of this Singapore Standard was approved on 31 March 2020 by the Chemical Standards Committee (CSC) under the purview of the Singapore Standards Council.

First published, 2013

First revision, 2020

CSC consists of the following members:

	Name	Representation
Chairman	: Dr Keith Carpenter	<i>Individual Capacity</i>
Deputy Chairman	: Er. Lucas Ng	<i>Individual Capacity</i>
Secretary 1	: Ms Elane Ng	<i>Standards Development Organisation @Singapore Chemical Industry Council</i>
Secretary 2	: Ms Rosmalinda Tay	<i>Standards Development Organisation @Singapore Chemical Industry Council</i>
Members	: Mr Goh Tiak Boon	<i>Individual Capacity</i>
	Prof Alfred Huan	<i>Individual Capacity</i>
	Er. Khong Beng Wee	<i>Individual Capacity</i>
	Mr Terence Koh	<i>Singapore Chemical Industry Council Limited</i>
	Dr Leong Kwai Yin	<i>Individual Capacity</i>
	Dr Thomas Liew	<i>National Metrology Centre</i>
	Mr Lim Eng Kiat	<i>Individual Capacity</i>
	Ms Jaime Lim	<i>Ministry of Manpower</i>
	Mr Lim Kian Chye / Mr Ng Eng Fu	<i>Housing & Development Board</i>
	Prof Loh Kian Ping	<i>National University of Singapore</i>
	Dr Loh Wah Sing	<i>Individual Capacity</i>
	Ms Pamela Phua	<i>Singapore Paint Industry Association</i>
	Mr Seah Khen Hee	<i>Individual Capacity</i>
	Assoc Prof Timothy Tan	<i>Nanyang Technological University</i>
	Dr Teo Tang Lin	<i>Chemical Metrology Division, Health Sciences Authority</i>
	Mr Yao Yikai	<i>Maritime and Port Authority of Singapore</i>
	Ms Suzanna Yap	<i>National Environment Agency</i>
Co-opted Members	: Ms Christina Loh	<i>Individual Capacity</i>
	Mr Pitt Kuan Wah	<i>Individual Capacity</i>

CSC sets up the Technical Committee on Surface Coatings to oversee the preparation of this standard. The Technical Committee consists of the following members:

	Name	Representation
Chairman	: Mr Lim Eng Kiat	<i>Individual Capacity</i>
Secretary	: Ms Wendy Chai	<i>Standards Development Organisation @Singapore Chemical Industry Council</i>
Members	: Mrs Grace Cheok-Chan	<i>Green Mark Department, Building and Construction Authority</i>
	Mr Leo Cher	<i>Singapore Green Building Council</i>
	Dr Dien Pandiman / Ms Sathammai Ramanathan	<i>Pidilite Innovation Centre Pte Ltd</i>
	Ms Stephanie Foo	<i>TÜV SÜD PSB Pte Ltd</i>
	Mr Ken Ho	<i>Building and Construction Authority</i>
	Dr K A Khider Mohamed	<i>Haruna Paint Pte Ltd</i>
	Mr Richard Lai	<i>Singapore Institute of Architects</i>
	Mr Lee Hong Wei	<i>Singapore Environment Council</i>
	Mr Lu Jin Ping	<i>AdMaterials Technologies Pte Ltd</i>
	Ms Pamela Phua	<i>Singapore Paint Industry Association</i>
	Mr Salim Suwignjo	<i>Setsco Services Pte Ltd</i>
	Mr Yap Chu Ing	<i>Housing & Development Board</i>
	Dr Yin Xi Jiang	<i>Singapore Surface Engineering Association</i>

The Technical Committee sets up the Working Group on Methods of Test for Paints, Varnishes and Related Materials to prepare this standard. The Working Group consists of the following experts who contribute in their *individual capacity*:

	Name
Convenor	: Dr Li Sihai
Members	: Ms Guo Yilin
	Dr K.A. Khider Mohamed
	Ms Calista Lee
	Mr Lee Weyliang
	Ms Shirley Lim
	Mr Simplicio Escano Sala

The organisations in which the experts of the Working Group are involved are:

AdMaterials Technologies Pte Ltd

Akzo Nobels Paints (Asia Pacific)

Haruna Paint Pte Ltd

Nippon Paint (Singapore) Co. Pte Ltd

Pidilite Innovation Centre Pte Ltd

Setsco Services Pte Ltd

TÜV SÜD PSB Pte Ltd

Contents	Page
National Forward.....	7
Foreword	8
Introduction	9
1. Scope	10
2. Normative references.....	10
3. Terms and definitions	11
4. Principle	12
5. Test solutions	12
5.1 Preparation of the sodium chloride solution.....	12
5.2 PH adjustment.....	123
5.2.1 pH of the salt solution.....	13
5.2.2 Neutral salt spray (NSS) test.....	13
5.2.3 Acetic acid salt spray (AASS) test	13
5.2.4 Copper-accelerated acetic acid salt spray (CASS) test.....	13
5.3 Filtration.....	13
6. Apparatus.....	13
6.1 Component protection	13
6.2 Spray cabinet	14
6.3 Heater and temperature control	14
6.4 Spraying device.....	14
6.5 Collecting devices.....	15
6.6 Re-use	15
7. Method for evaluating cabinet corrosivity.....	16
7.1 General.....	166
7.2 Reference specimens	16
7.3 Arrangement of the reference specimens.....	16
7.4 Determination of mass loss (mass per area).....	177
7.5 Satisfactory performance of cabinet.....	17
8. Test specimens.....	17
9. Arrangement of the test specimens.....	18
10. Operating conditions	18
11. Duration of tests	19
12. Treatment of test specimens after test.....	19
12.1 General.....	19

12.2	Non-organic coated test specimens: metallic and/or inorganic coated.....	19
12.3	Organic coated test specimens.....	20
12.3.1	Scribed organic coated test specimens	20
12.3.2	Organic coated but not scribed test specimens.....	20
13.	Evaluation of results	20
14.	Test report.....	21
Annex A (informative)	Example schematic diagram of one possible design of spray cabinet with means for optional treating fog exhaust and drain	22
Annex B (informative)	Complementary method for evaluating cabinet corrosivity using zinc reference specimens.....	24
B.1	Reference specimens	24
B.2	Arrangement of the reference specimens.....	24
B.3	Determination of mass loss	24
B.4	Satisfactory performance of cabinet.....	25
Annex C (normative)	Preparation of specimens with organic coatings for testing	26
C.1	Preparation and coating of specimens	26
C.2	Drying and conditioning.....	26
C.3	Thickness of coating.....	26
C.4	Preparation of scribe marks	26
Annex D (normative)	Required supplementary information for testing test specimens with organic coatings.....	27
Bibliography	28

National Foreword

This Singapore Standard was prepared by the Working Group on Methods of Test for Paints, Varnishes and Related Materials set up by the Technical Committee on Surface Coatings under the purview of CSC.

It is a revision of SS 5 : Part G10 : 2013 “Methods of test for paints, varnishes and related materials – Part G10: Corrosion tests in artificial atmospheres – Salt spray tests”.

This standard is a modified adoption of ISO 9227:2017, “Corrosion tests in artificial atmospheres – Salt spray tests”, published by the International Organization for Standardization. The deviation is as follows:

Subclause	Modification
C.2	Replace “(23 ± 2) °C and a relative humidity of (50 ± 5) %” with “(27 ± 2) °C and a relative humidity of (80 ± 5) %”.
	<i>Explanation:</i> To reflect the local climatic conditions.

To facilitate identification, the technical deviation is marked by a margin on the left of the standard.

NOTE 1 – Reference to International Standards are replaced by applicable Singapore Standards/Technical References.

NOTE 2 – Where numerical values are expressed as decimals, the comma is read as a full point.

For an overview of other parts to Singapore Standard 5, it is recommended to read the information in SS 5 : Part 0 “General introduction” which is issued separately.

This standard is expected to be used by paint, coatings and inks manufacturers, materials suppliers, test laboratories and related government agencies.

Attention is drawn to the possibility that some of the elements of this Singapore Standard may be the subject of patent rights. Enterprise Singapore shall not be held responsible for identifying any or all of such patent rights.

NOTE

1. Singapore Standards (SSs) and Technical References (TRs) are reviewed periodically to keep abreast of technical changes, technological developments and industry practices. The changes are documented through the issue of either amendments or revisions. Where SSs are deemed to be stable, i.e. no foreseeable changes in them, they will be classified as “Mature Standards”. Mature Standards will not be subject to further review, unless there are requests to review such standards.
2. An SS or TR is voluntary in nature except when it is made mandatory by a regulatory authority. It can also be cited in contracts making its application a business necessity. Users are advised to assess and determine whether the SS or TR is suitable for their intended use or purpose. If required, they should refer to the relevant professionals or experts for advice on the use of the document. Enterprise Singapore and the Singapore Standards Council shall not be liable for any damages whether directly or indirectly suffered by anyone or any organisation as a result of the use of any SS or TR. Although care has been taken to draft this standard, users are also advised to ensure that they apply the information after due diligence.
3. Compliance with a SS or TR does not exempt users from any legal obligations.

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 156, *Corrosion of metals and alloys*.

This fourth edition cancels and replaces the third edition (ISO 9227:2012), which has been technically revised. The main technical changes are as follows:

- new definitions for reference material, reference specimen, test specimen and substitute specimen have been implemented;
- checking of the test apparatus during test operation has been made possible;
- Clause 4 has been added, with some of its text moved from the scope;
- Clause 7 has been summarized.

Introduction

There is seldom a direct relation between resistance to the action of salt spray and resistance to corrosion in other media, because several factors influencing the progress of corrosion, such as the formation of protective films, vary greatly with the conditions encountered. Therefore, the test results should not be regarded as a direct guide to the corrosion resistance of the tested metallic materials in all environments where these materials might be used. Also, the performance of different materials during the test should not be taken as a direct guide to the corrosion resistance of these materials in service.

Nevertheless, the method described gives a means of checking that the comparative quality of a metallic material, with or without corrosion protection, is maintained.

Different metallic substrates (metals) cannot be tested in direct comparison in accordance to their corrosion resistances in salt spray tests. Comparative testing is only applicable for the same kind of substrate.

Salt spray tests are generally suitable as corrosion protection tests for rapid analysis for discontinuities, pores and damage in organic and inorganic coatings. In addition, for quality control purposes, comparison can be made between specimens coated with the same coating. As comparative tests, however, salt spray tests are only suitable if the coatings are sufficiently similar in nature.

It is often not possible to use results gained from salt spray testing as a comparative guide to the long-term behaviour of different coating systems, since the corrosion stress during these tests differs significantly from the corrosion stresses encountered in practice.

Methods of test for paints, varnishes and related materials – Part G10 : Corrosion tests in artificial atmospheres — Salt spray tests

1 Scope

This document specifies the apparatus, the reagents and the procedure to be used in conducting the neutral salt spray (NSS), acetic acid salt spray (AASS) and copper-accelerated acetic acid salt spray (CASS) tests for assessment of the corrosion resistance of metallic materials, with or without permanent or temporary corrosion protection.

It also describes the method employed to evaluate the corrosivity of the test cabinet environment.

It does not specify the dimensions or types of test specimens, the exposure period to be used for a particular product, or the interpretation of results. Such details are provided in the appropriate product specifications.

The salt spray tests are particularly useful for detecting discontinuities, such as pores and other defects, in certain metallic, organic, anodic oxide and conversion coatings.

The neutral salt spray (NSS) test particularly applies to

- metals and their alloys,
- metallic coatings (anodic and cathodic),
- conversion coatings,
- anodic oxide coatings, and
- organic coatings on metallic materials.

The acetic acid salt spray (AASS) test is especially useful for testing decorative coatings of copper + nickel + chromium, or nickel + chromium. It has also been found suitable for testing anodic and organic coatings on aluminium.

The copper-accelerated acetic acid salt spray (CASS) test is useful for testing decorative coatings of copper + nickel + chromium, or nickel + chromium. It has also been found suitable for testing anodic and organic coatings on aluminium.

The salt spray methods are all suitable for checking that the quality of a metallic material, with or without corrosion protection, is maintained. They are not intended to be used for comparative testing as a means of ranking different materials relative to each other with respect to corrosion resistance or as means of predicting long-term corrosion resistance of the tested material.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1514, *Paints and varnishes — Standard panels for testing*

ISO 2808, *Paints and varnishes — Determination of film thickness*

ISO 3574, *Cold-reduced carbon steel sheet of commercial and drawing qualities*

ISO 4623-2:2016, *Paints and varnishes — Determination of resistance to filiform corrosion — Part 2: Aluminium substrates*

ISO 4628-1, *Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 1: General introduction and designation system*

ISO 4628-2, *Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 2: Assessment of degree of blistering*

ISO 4628-3, *Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 3: Assessment of degree of rusting*

ISO 4628-4, *Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 4: Assessment of degree of cracking*

ISO 4628-5, *Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 5: Assessment of degree of flaking*

ISO 4628-8, *Paints and varnishes — Evaluation of degradation of coatings — Designation of quantity and size of defects, and of intensity of uniform changes in appearance — Part 8: Assessment of degree of delamination and corrosion around a scribe or other artificial defect*

ISO 8044, *Corrosion of metals and alloys — Basic terms and definitions*

ISO 8407, *Corrosion of metals and alloys — Removal of corrosion products from corrosion test specimens*

ISO 8993, *Anodizing of aluminium and its alloys — Rating system for the evaluation of pitting corrosion — Chart method*

ISO 10289, *Methods for corrosion testing of metallic and other inorganic coatings on metallic substrates — Rating of test specimens and manufactured articles subjected to corrosion tests*

ISO 17872, *Paints and varnishes — Guidelines for the introduction of scribe marks through coatings on metallic panels for corrosion testing*